

# ACSO 1 RGB

## L601.

Spot encastrable piétable avec trois POWER LED RGB, bride plate en acier tourné électropoli, corps dissipateur en aluminium, verre trempé et optique secondaire au choix. Peut être installé au sol, au mur ou au plafond à l'extérieur. Pour l'éclairage de la végétation des jardins ou de façades architecturales.

- Testé et fourni avec des câbles de 0,7 m et câblage IN/OUT.
- Alimentation: 350mA
- Câble: 70 cm + connecteurs

RACCORDER et METTRE SOUS TENSION d'après les plans de montage.

*Recessed walkover spot light with three RGB POWER LED, flat electropolished and turned steel flange, dissipating aluminium body, tempered glass and choice of secondary optic.*

*It can be floor, wall or ceiling installed on outdoor locations.*

*It is suitable for illumination of gardens or for architectural facades.*



- *Tested and supplied with 0,7m cables and IN/OUT wiring.*
- *Power supply: 350mA.*
- *Wire cm 70 with connectors*

*CONNECT and SUPPLY POWER as shown on assembly scheme.*




### DIMENSIONS / DIMENSIONS


### ACCESSOIRES / ACCESSORIES



Boîtier d'enc. **548/80** p. 296  
Outer casing 548/80 page 296



Anneau avec ressorts **TES0065**  
Ring with springs TES0065



Drivers (p. 260).  
Drivers page 260



Système de contrôle LED RGB p. 273  
RGB LED control system page 273

### CODES DE BASE / BASE CODES

### FAISCEAU LUMINEUX / LIGHT BEAM

### VERRE / GLASS

### COULEUR LED / LED COLOR

### PUISSANCE / POWER

**L601.**

- 15 15°
- 25 25°
- 40 40°
- 60 60°
- 80 80°

- T Transparent / Transparent
- S Sablé / Sandblasted

■ RGB Tricolore RGB

3X1W 350mA

Exemple de codification: Article ACSO 1 RGB + Faisceau lumineux 15° + Verre transparent + Couleur led Tricolore RGB = Code : **L601.15TRGB**  
Example of codification: Product ACSO 1 RGB + Light beam 15° + Glass transparent + Led color Tricolor RGB = Code: **L601.15TRGB**