

Spot encastrable avec un POWER LED RGB, corps en polycarbonate traité ou transparent et optique secondaire au choix. Encastrable, grâce aux ressorts ; en appui, grâce à l'accessoire de support. Parfait pour l'éclairage décoratif des espaces, à appliquer sur les étagères, les armoires, les rayons, les bibliothèques et le placo-plâtre.

- Testé et fourni avec des câbles de 0,7 m et un câblage IN/OUT
- Ressorts inclus

RACCORDER et METTRE SOUS TENSION d'après les plans de montage.

Recessed spot light with one RGB POWER LED, with treated polycarbonate or transparent body and choice of secondary optic. It can be recessed thanks to springs or can be lay-in installed with accessorial support.

It is especially suitable for rooms decorations to apply on shelves, wardrobes, bookcases and drywall.


- Tested and supplied with 0,7m cables and IN/OUT wiring.
- Fixing spring enclosed

CONNECT and SUPPLY POWER as shown on assembly scheme.




DIMENSIONS / DIMENSIONS

ACCESSOIRES / ACCESSORIES



Système de contrôle LED RGB p. 273
RGB LED control system page 273



Drivers (p. 260).
Drivers page 260

CODES DE BASE / BASE CODES

L95.

FINITIONS / FINISHINGS

- 1 Blanc / White
- 2 Noir / Black
- 3 Or brossé / Satin gold
- 6 Chrome / Chrome
- 7 Aluminium brossé / Satin aluminium
- 8 Transparent / Transparent
- 9 Or brillant / Polish gold

FAISCEAU LUMINEUX / LIGHT BEAM

- 15 15°
- 25 25°
- 40 40°
- 60 60°
- 80 80°
- ELL Elliptique 25°x45

COULEUR LED / LED COLOR

RGB Full-Color RGB

PUISSANCE / POWER

1x3W 350mA

Exemple de codification: Article EOS RGB + Finition aluminium + Faisceau lumineux 15° + Couleur led full color RGB = **Code : L95.715RGB**

Example of codification: Product EOS RGB + Finishing aluminium + Light beam + Led color full-color RGB = Code: L95.715RGB