

# IRIDE-W

## L9912.

Élément encastrable thermoplastique moulé avec LED WICOP.  
Pour l'éclairage d'accentuation, de décoration ou de courtoisie.  
Peut être installé à l'intérieur.

- Montage par pression.
- Diffusion full Light.
- Alimentation: 12Vcc
- Câble: 50cm
- Ressorts inclus

À CONNECTER EN PARALLÈLE

*Thermoplastic printed recessed spot with WICOP LED.*

*It is suitable as accent lighting, as decoration or as curtesy light.  
It can be installed on indoor locations.*

- Pressure assembly.
- Full light diffusion.
- Power supply: 12Vdc
- Cable: cm. 50
- Springs included

CONNECT IN PARALLEL



# ZEFIRO-W

## L9812.

Élément encastrable thermoplastique moulé avec LED WICOP.  
Pour l'éclairage d'accentuation, de décoration ou de courtoisie.  
Peut être installé à l'intérieur.

- Montage par pression.
- Diffusion full Light.
- Alimentation: 12Vcc
- Câble: 50cm
- Ressorts inclus

À CONNECTER EN PARALLÈLE

*Thermoplastic printed recessed spot with WICOP LED.*

*It is suitable as accent lighting, as decoration or as curtesy light.  
It can be installed on indoor locations.*


- Pressure assembly.
- Full light diffusion.
- Power supply: 12Vdc
- Cable: cm. 50
- Springs included

CONNECT IN PARALLEL




### DIMENSIONS / DIMENSIONS


#### L9912.



#### L9812.



### ACCESSOIRES / ACCESSORIES



Ballasts (p. 258).  
Drivers page 258

### CODES DE BASE / BASE CODES

## L9912. L9812.

### FINITIONS FINISHINGS

- 1 Blanc / White
- 2 Noir / Black
- 3 Or brossé / Satin gold
- 6 Chrome / Chrome
- 7 Aluminium brossé / Satin aluminum
- 8 Transparent / Transparent
- 9 Or brillant / Polish gold

### COULEUR LED / LED COLOR

- BN 4000°K
- BC 3000°K
- CC 2700°K

### PUISSANCE / POWER

2W - 12Vcc - 216 lm

Exemple de codification : Article IRIDE W + Finition blanc + Couleur led 3000°K = Code : L9912.1BC  
Example of codification: Product IRIDE W + Finishing white + Led color 3000°K = Code: L9912.1BC